A38E
ELECTRIC BOOM LIFT

APA
ACCESS PLATFORMS ABERDEEN

215KG
Lift Capacity

13.50M
Working Height

6.10M
Horizontal Outreach

snorkel




Compact electric boom lift offering versatile indoor and light outdoor access with smooth operation and reliable manoeuvrability.

[BENEFITS]

- Popular electric articulatedboom lift
- Lightweight, durable and reliable
- Smooth, easy to use controls
- Compact chassis for excellent manoeuvrability
- Suitable for indoor and outdoor use

[TECHNICAL DATA]

WORKING HEIGHT	13.50 m
DRIVE HEIGHT	11.50 m
LIFT CAPACITY	215 kg
HORIZONTAL OUTREACH	6.10 m
UP AND OVER CLEARANCE	5.40 m
A PLATFORM HEIGHT	11.50 m
B WIDTH	1.50 m
C LENGTH	4.10 m
D HEIGHT - STOWED	2 m
E X F PLATFORM SIZE	0.69 x 1.11 m
GROUND CLEARANCE	12 cm
TAILSWING - RISER BOOM ELEVATED	0 m
TAILSWING - RISER BOOM STOWED	1.4 m
RAISE/LOWER TIME	83/68 sec
PLATFORM ROTATION	90° (+45°/-45°)
TURRET ROTATION	360° (non continuous)
TURNING RADIUS - OUTSIDE	2.4 m
TURNING RADIUS - INSIDE	1.12 m
MAX WIND SPEED	12.5 m/s
DRIVE SPEED - STOWED	4.0 km/h
DRIVE SPEED - ELEVATED	0.6 5km/h
GRADEABILITY	36 %
TYRES - NON MARKING	22 x 9 16
CONTROLS	Proportional
DRIVE SYSTEM	Direct Drive DC
POWER SOURCE	8 x 6 V, 220 Ah battery
BATTERY CHARGER	100 - 200 V / 15 A
WEIGHT	3 880 kg



[STANDARD FEATURES]

- Snorkel Guard™ secondary guarding system
- Proportional one-handed controls
- Hydraulic platform rotation
- Minimal front boom overhang
- Ultra-tight inside turning radius
- Power line to platform
- Tilt alarm and cut-out
- 2 person indoor
- 1 person outdoor
- Direct DC drive series wired wheel motors
- Non-marking tyres
- Duplicate boom controls at ground level
- Hour meter and on-board diagnostics display
- Flashing amber light
- 2 year parts and labour, 5 year structural warranty
- CE approved

[OPTIONS AND ACCESSORIES]

- Special paint colours
- Environmental hydraulic oil
- Snorkel OnSite™ telematics