HA12 PX
DIESEL BOOM LIFT

APA
ACCESS PLATFORMS ABERDEEN

230KG
Lift Capacity

12.40M
Working Height

6.60M
Horizontal Outreach

Haulotte GROUP




Compact articulated diesel boom lift delivering reliable outreach and rough terrain performance for flexible access on uneven outdoor sites.

[BENEFITS]

- Hydraulic differential lock and 11 in (29 cm) ground clearance for improved rough terrain capability
- 11 ft 3 in (3.45 m) turning radius and 5ft 9 in (1.80 m) width for improved manoeuverability
- Full proportional controls for all movements
- Simple uncomplicated operational controls
- Work platform overload limiter increases safety
- Robust, reliable and easy to maintain design

[TECHNICAL DATA]

WORKING HEIGHT	12.40 m
PLATFORM HEIGHT	10.40 m
HORIZONTAL OUTREACH	6.60 m
UP AND OVER CLEARANCE	5.25 m
LIFT CAPACITY	230 kg
A LENGTH	5.64 m
B WIDTH	1.80 m
C HEIGHT - STOWED	2.15 m
D WHEELBASE	1.94 m
E GROUND CLEARANCE	29 cm
F X G PLATFORM SIZE	1.20 x 0.80 m
LENGTH - TRANSPORT	5.50 m
HEIGHT - TRANSPORT	2.15 m
TAILSWING	0 cm
FLY JIB RANGE OF MOTION	140° (-70° / +70°)
FLY JIB LENGTH	1.50 m
HYDRAULIC PLATFORM ROTATION	180°
TURNTABLE ROTATION	360°
TURNING RADIUS - OUTSIDE	3.45 m
TURNING RADIUS - INSIDE	1.55 m
PROPORTIONAL DRIVE SPEED	0.75 km/h - 4.5 km/h
GRADEABILITY	40 %
TYRES - FOAM FILLED	10.5/80 - 18/10
ENGINE	Diesel 31 CV - 21 kw
HYDRAULIC CAPACITY	100 l
FUEL CAPACITY	65 l
WEIGHT	5 640 kg



[STANDARD FEATURES]

- 4 wheel drive and 2 back steering wheels
- Diesel engine
- 230 V - 50 Hz / 120 V - 60 Hz power line to cage
- 5° tilt alarm
- Safe use in winds up to 28 mph (45 km/h)
- 12 V - 95 A battery / electrical control system
- Load limiter in cage
- Emergency hand pump
- Free wheeling device
- Hourmeter
- Mechanical turret slewing lock
- Towing hooks / lifting eyes
- 2 hooks for safety harness in cage

[OPTIONS AND ACCESSORIES]

- Travel/motion alarm
- Rotating beacon
- Working light
- Hydraulic oil cooler
- Power line to cage
- Biodegradable oil for warm and cold countries
- 12 x 18 large tyres