PECOLIFT
PUSH AROUND LIFT

APA
ACCESS PLATFORMS ABERDEEN

150KG
Lift Capacity

3.50M
Working Height

1.50M
Platform Height

pecolift
3.5m Non-Powered, Powered Access



Compact, battery-free push-around lift providing simple, safe low-level access with instant elevation and minimal maintenance in tight indoor spaces.

[BENEFITS]

- Eco friendly
- Battery free
- Power free
- Oil free
- Step into the platform, no climbing
- Intuitive to operate - turn handle to elevate. Patented* lift mechanism, no power required
- 'Auto-lok' brake on elevation
- Lightweight, easy to manoeuvre
- Small footprint
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

*patent applied for

[TECHNICAL DATA]

WORKING HEIGHT	3.50 m
PLATFORM HEIGHT	1.50 m
LIFT CAPACITY	150 kg (1 pers + tools)
BASKET DIMENSIONS	0.72 m (L) x 0.60 m (W)
WORKING FOOTPRINT	0.98 m x 0.70 m
MAXIMUM MANUAL FORCE	200 N
MAXIMUM GRADIENT FOR OPERATION	0°
MAXIMUM WIND FORCE	Internal use, 0 mph
MAXIMUM WHEEL FORCE	125 kg
MAXIMUM CASTOR POINT LOAD	125 kg (1.23 kN)
SOUND PRESSURE LEVEL	Less than 70Dba
LENGTH - CLOSED	0.98 m
WIDTH - CLOSED	0.70 m
HEIGHT - CLOSED	1.55 m
WEIGHT - CLOSED	180 kg
LIFT CYCLES	Unlimited



[STANDARD FEATURES]

- Non-powered access
- Unlimited lift cycles
- Auto-lok brake
- Step-in entry
- Lift capacity 150 kg (1 person + tools)
- Reaches full working height in 11 sec

[OPTIONS AND ACCESSORIES]

- Wind rated available as an option to the standard machine, Pecolift Wind Rated is operable on gradients up to 3° and in winds up to 28mph