POWER TOWER
PUSH AROUND LIFT

APA
ACCESS PLATFORMS ABERDEEN

250KG
Lift Capacity

5.10M
Working Height

3.10M
Platform Height

POWER TOWER
The Powered Scaffold Tower



Powered push-around lift with larger platform space, delivering stable low-level access and increased working room for tools and materials.

[BENEFITS]

- Compact
- Cost effective
- Safe
- Efficient
- Passes easily through single doorway or into passenger lifts
- Easy tail-lift transportation
- Suspended ceiling grid, narrow basket (option)

[TECHNICAL DATA]

WORKING HEIGHT	5.10 m
PLATFORM HEIGHT	3.10 m
LIFT CAPACITY	250 kg
PLATFORM DIMENSIONS	1.52 m x 0.75 m
WORKING FOOTPRINT	1.60 m x 0.78 m
LENGTH	1.60 m
WIDTH	0.78 m
HEIGHT	1.85 m
BATTERY	12 V c/w Automatic charger
MAINS	110 V or 230 V
CONTROLS	Simple push button basket controls
WEIGHT	342 kg





[STANDARD FEATURES]

- Fail-safe hydraulic circuit complete with check valve on lift cylinder
- Improved heavy-duty Auto-lok wheels on elevation provide secure base
- Emergency descent from ground level
- Audible ascent and descent drive alarm
- Powered push-around lift with larger platform space, delivering stable low-level access and increased working room for tools and materials
- 250 kg safe working load (1 pers)
- Easy access gate
- Larger chassis fork truck pockets
- Improved power input interface

[OPTIONS AND ACCESSORIES]

- Tilt alarm c/w auto cut-out
- Narrow basket for suspended ceiling grid access
- Pipe carrying kit (max 2” pipe)
- Tool tray
- Foam buffer kit