SNORKEL S2755RT
DIESEL SCISSOR LIFT

ACCESS PLATFORMS ABERDEEN

300KG	10.10M	8.10M
Lift Capacity	Working Height	Platform Height

snorkel



Compact rough terrain scissor lift providing reliable height access, strong stability and manoeuvrability in confined outdoor environments.

[BENEFITS]


- Narrow compact diesel rough terrain scissor lifts
- Excellent rough terrain performance
- Easy to operate
- Roll-out deck extension for extra reach
- Ideal for outdoor work in confined spaces

KEEPING SCOTLAND SAFE AT HEIGHT

ACCESSABERDEEN.CO.UK

[TECHNICAL DATA]

WORKING HEIGHT	10.10 m
DRIVE HEIGHT	7.80 m
LIFT CAPACITY	300 kg
A PLATFORM HEIGHT	8.10 m
PLATFORM SIZE - STOWED	1.40 x 2.73 m
PLATFORM SIZE - EXTENDED	1.40 x 3.93 m
B OVERALL WIDTH	1.45 m
C OVERALL LENGTH	3.30 m
EXTENSION DECK LENGTH	1.20 m
D STOWED HEIGHT	2.50 m
MIN HEIGHT - GUARDRAILS FOLDED	2.13 m
GROUND CLEARANCE	26 cm
RAISE/LOWER TIME	26/30 sec
MAX OUTRIGGER LEVELLING - FRONT TO REAR	6°
MAX OUTRIGGER LEVELLING - SIDE TO SIDE	10°
TURNING RADIUS - OUTSIDE	4.75 m
TURNING RADIUS - INSIDE	2.50 m
EXIT/ENTRY ANGLE	20°
MAX WIND SPEED	12.5 m/s
DRIVE SPEED - STOWED	5.2km/h
DRIVE SPEED - ELEVATED	0.5km/h
GRADEABILITY	35%
TYRES - NON MARKING	0.58m x 0.22m - 12
CONTROLS	Proportional joystick
DRIVE SYSTEM	4-wheel drive
POWER SOURCE	Kubota diesel engine
WEIGHT	2 750kg



[STANDARD FEATURES]

- 4-wheel drive
- 4 hydraulic outriggers with automatic levelling
- Roll-out deck extension
- Proportional controls
- Non-marking tyres
- Power line to platform
- Drive motion alarm
- Descent alarm
- Manual lowering valve
- Flashing amber light
- Dual lanyard attachment points
- Oscillating axle
- Hour meter
- 2 year parts & labour, 5 year structural warranty
- CE approved

[OPTIONS AND ACCESSORIES]

- Special paint colours
- Nylon spreader pads (set of 4)
- Environmental hydraulic oil
- Cold weather package
- Snorkel OnSite™ telematics